

# **PRODUCT DATASHEET**RF1906 CLAS ST 25 5 W/2000 K E27

Vintage 1906 LED | LED lamps, vintage edition



## **AREAS OF APPLICATION**

- Domestic applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)
- Perfect for decorative installations

#### **PRODUCT BENEFITS**

- Very low energy consumption
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lamps with innovative LED "filament" technology

#### **PRODUCT FEATURES**

- LED lamps for line voltage
- Mercury-free lamps
- Lifetime: up to 15,000 h
- Beam angle: up to 360°



# **TECHNICAL DATA**

## Electrical data

Rated wattage	5.00 W
Nominal wattage	5.00 W
Nominal voltage	220240 V
Max. lamp no. on circuit break. 10 A (B)	18
Max. lamp no. on circuit break. 16 A (B)	29
Operating frequency	5060 Hz
Power factor $\lambda$	> 0.50
Claimed equiv. conventional lamp power	25 W


#### Photometrical data

Nominal luminous flux	250 lm
Rated luminous flux	250 lm
Kateu tullillious Itux	250 till
Rated color temperature	2000 K
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2000 K
Luminous flux	250 lm
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcm

# Light technical data

Warm-up time (60 %)	< 0.50 s	
Starting time	< 0.5 s	

# Dimensions & weight



Overall length	140.0 mm
Diameter	64.0 mm

Outer bulb	-
Length	140.0 mm

# Temperatures & operating conditions

Maximum temperature at tc test point 56 °C	
--	--

#### Lifespan

Nominal lamp life time	15000 h
Rated lamp life time	15000 h
Number of switching cycles	100000

## Additional product data

Base (standard designation)	E27	
Mercury content	0.0 mg	
Mercury-free	Yes	
Show WEEE picto	Yes	
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	

## Capabilities

Dimmable	No

# Certificates & standards

Energy efficiency class	Α
Energy efficiency class	A
Energy consumption	5 kWh/1000h

#### Country-specific categorizations

rder reference	1906LEDISON 5W/
----------------	-----------------

## **LOGISTICAL DATA**

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075092112	RF1906 CLAS ST 25 5 W/2000 K E27	Shipping carton box 4	185 mm x 185 mm x 206 mm	7.05 dm³	492.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.