




Suspension | 220-240 V | topLED 96 W 1800 mA | DALI | CRI 90  
**7788N**



Données techniques	
Position d'installation	Plafond
Environnement d'installation	Intérieur
Source lumineuse	LED
Optique	General Lighting
Light emission direction	downward and upward
Puissance	96 W
Flux lumineux (source)	13965 lm
Frequency	60 - 50 Hz
Température de couleur / Tonalità	4000 K
Indice de rendu chromatique	90 Ra
Classe d'isolation	1
IP	IP20
Essai au fil incandescent	650°
Montage direct sur des surfaces normalement inflammables	Oui
CE	Oui
ETL	Non
Driver inclus	Oui
Article à intensité variable	DALI
Induzione	Non
Mode de secours	Non
Motion sensor	Non
Orientable	Non
Basculement	Non
Piétinable	Non
Carrossable	Non
Câble inclus	Non
Revêtement en résine	Non
Poids net	11.2 Kg

Finition diffuseur	
Matériau	PE
Couleur	neutre
Finition monture	
Matériau	Fer
Couleur	blanc gaufré RAL 9003
Fabrication	Vernissage



Suspension | 220-240 V | topLED 96 W 1800 mA | DALI | CRI 90  
**7788N**

Single emission pendant luminaires for indoor application. The warm white LED light source with a general lighting light distribution is composed of 108 topped LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 13965 lm, with a 145.5 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The diffuser is made of pe; the mounting frame is made of iron, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 11.2 kg. The power supply driver is included in the delivery.

The total absorbed power is 96 W.

The device features protection class I and can be ceiling-mounted.

Caractéristiques Techniques de l'éclairage	
Flux lumineux (source)	13965 lm
Température de couleur	4000 K
Standards de Concordance de Couleur	3 Step MacAdam
Indice de rendu chromatique	90 Ra
Life / Failure ratio	L80C0B20 80H