






ROBY

CEILING SURFACE



1.6

LED 12W | 220-240VAC | 50-60Hz
PCB 3-step | phase-cut dim
aluminium powder coated
brushed | opal PMMA cover

1.00kg IP44

2700K | >80 CRI | 750lm

CODE
135184W2

3000K | >80 CRI | 820lm

CODE
135184W4
135184L4

OPTIONAL

dimmer
CODE
for switch 90019017
for din rail 90019018

more specs on page 576

2.6

LED 18W | 220-240VAC | 50-60Hz
PCB 3-step | phase-cut dim
aluminium powder coated
brushed | opal PMMA cover

1.55kg IP44

2700K | >80 CRI | 1080lm

CODE
135284W2

3000K | >80 CRI | 1220lm

CODE
135284W4
135284L4

OPTIONAL

dimmer
CODE
for switch 90019017
for din rail 90019018

more specs on page 576

3.5

LED 32W | 220-240VAC | 50-60Hz
PCB 3-step | phase-cut dim
aluminium powder coated
brushed | opal PMMA cover

2.45kg IP44

2700K | >80 CRI | 1820lm

CODE
135384W2

3000K | >80 CRI | 1950lm

CODE
135384W4
135384L4

OPTIONAL

dimmer
CODE
for switch 90019017
for din rail 90019018

more specs on page 576