

PRODUCT DATASHEETLinear LED Flat 6 W 4000 K

Linear LED Flat | Slim undercabinet luminaire for surface mounting

AREAS OF APPLICATION

- Undercabinet lighting



PRODUCT BENEFITS

- Connection of up to 43 (ECO version) or 18 (sensor Version) luminaires in a row
- Various accessories included: cables and connectors



TECHNICAL DATA

Electrical data

Nominal wattage	6.00 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 K
Color rendering index Ra	>80
Light color (designation)	Cool White
Luminous flux	320 lm

Dimensions & weight



Length	370.0 mm
Width	67.0 mm
Height	22.0 mm
Product weight	325.00 g

Colors & materials

Body material Aluminum	
Housing color	Silver
Product color	Silver
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-2040 °C
---------------------------	----------

Additional product data

Mounting type	Surface
---------------	---------

Mounting location	Cabinet undersides

Capabilities

Dimmable	No	
Type of connection	Plug, EU	
LED module replaceable	Not replaceable	

Certificates & standards

Protection class	II	
Type of protection	IP20	
Standards	CE/EAC/REACH/RoHS	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075264328	Folding carton box 1	38 mm x 71 mm x 400 mm	339.00 g	1.08 dm ³
4058075264335	Shipping carton box 8	416 mm x 303 mm x 92 mm	3151.00 g	11.60 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.