

PRODUCT DATASHEET SubMARINE Integrated Slim Value 600 10 W 4000

SubMARINE Integrated Slim Value | Flat and slim dampproof luminaires with integrated LED module

AREAS OF APPLICATION

- Basements, garages, warehouses



- Easy installation, no tools required for connection
- Impressive for its low-profile design

PRODUCT FEATURES

- Damp-proof luminaires
- Dust-protected and jet-proof (IP65)
- Extremely low profile
- Not dimmable



TECHNICAL DATA


Electrical data

Nominal wattage	10.00 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 К
Color rendering index Ra	≥80
Light color (designation)	Cool White
Luminous flux	900 lm
Luminous efficacy	90 lm/W

Dimensions & weight



Length	715.0 mm
Width	53.0 mm
Height	35.0 mm
Product weight	194.00 g

Colors & materials

Body material	Polycarbonate (PC)	
Housing color	White	
Product color	White	

Temperatures & operating conditions

Ambient temperature range	-2035 °C
---------------------------	----------

Additional product data

Mounting type	Surface
---------------	---------

Capabilities

Dimmable	No
Type of connection	Terminal, 2-Pole (L, N)
LED module replaceable	Not replaceable

Certificates & standards

Protection class	11
Type of protection	IP65
Standards	CE/EAC/REACH/RoHS

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075266391	Folding carton box 1	42 mm x 58 mm x 702 mm	213.00 g	1.71 dm³
4058075266407	Shipping carton box 20	750 mm x 249 mm x 225 mm	4809.00 g	42.02 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.