

# PRODUCT DATASHEET

## CABINET LED Corner 550

Cabinet LED Corner | Low voltage undercabinet luminaires for corner application

---

### AREAS OF APPLICATION

- Shelf and undercabinet lighting



---

### PRODUCT BENEFITS

- Low voltage luminaire for DC operation with external driver
- Suitable for mounting in corners
- Homogenous light distribution
- Easy and fast mounting on nearly every surface (adhesive tape or screws)

---

### PRODUCT FEATURES

- Luminous flux: up to 480 lm
- Switch on and off by movements with 5 cm distance in front of the infrared motion sensor
- Stepless dimming by covering the infrared motion sensor in 5 cm distance for at least one second
- Material: aluminum
- Color: silver
- Available in two lengths: 35 cm and 55 cm
- Available as single and double luminaire kit



**TECHNICAL DATA**

Electrical data

Nominal wattage	7.50 W
Operating mode	External LED driver
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 K
Color rendering index Ra	≥80
Light color (designation)	Warm White
Luminous flux	480 lm
Luminous efficacy	64 lm/W

Luminaire sensor data

Sensor technology	Infrared/Photocell
Detection range of motion sensor	5 cm

Dimensions & weight



Length	550.0 mm
Width	40.7 mm
Height	23.0 mm
Product weight	335.00 g
Cable length	1500 mm

Colors & materials

Body material	POLYCARBON. (PC)/ACRYLONIT.
Housing color	Gray
Product color	Gray

<b>Cover material</b>	Polycarbonate (PC)
-----------------------	--------------------

### Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...+40 °C
----------------------------------	--------------

### Additional product data

<b>Mounting type</b>	Surface
<b>Mounting location</b>	Cabinet undersides

### Capabilities

<b>Dimmable</b>	Yes
<b>Type of connection</b>	Plug, EU
<b>LED module replaceable</b>	Not replaceable

### Certificates & standards

<b>Protection class</b>	II
<b>Type of protection</b>	IP20
<b>Standards</b>	CE/RoHS/EAC

### EQUIPMENT / ACCESSORIES

- External mains adapter (cable length: 1.5 m) included

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075227958	Folding carton box 1	71 mm x 71 mm x 629 mm	412.00 g	3.17 dm <sup>3</sup>
4058075227965	Shipping carton box 8	644 mm x 303 mm x 159 mm	3794.00 g	31.03 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.