

PRELIMINARY-PRODUCT DATASHEET LED WORKLIGHT S-STAND 50 W 4000 K

LED Worklights S-STAND | Portable LED Worklight with S-Stand



AREAS OF APPLICATION

- Outdoor
- Parks
- Garages
- Basement
- Workshops
- Renovation

PRODUCT BENEFITS

- Optimized weight and size due to compact design
- Very homogenous light
- Energy-efficient thanks to LED technology

PRODUCT FEATURES

- Very bright and functional outdoor LED luminaires
- Type of protection: IP65
- Die-cast aluminum housing
- Quick-release fastener for adjustment of luminaire head angle
- 2 m cable with Schuko plug (type F)



TECHNICAL DATA


Electrical data

Nominal wattage	50.00 W
Operating mode	Electronic control gear (ECG)
Nominal voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 К
Color rendering index Ra	≥80
Light color (designation)	Cool White
Luminous flux	4500 lm
Luminous efficacy	90 lm/W

Dimensions & weight



Length	267.0 mm
Width	272.0 mm
Height	395.0 mm
Product weight	1930.00 g

Colors & materials

Body material	Aluminum/Steel
Housing color	Dark gray
Product color	Dark gray
Cover material	Glass

Temperatures & operating conditions

Ambient temperature range	-20+45 °C
---------------------------	-----------

Additional product data

Mounting type	Standing
Mounting location	Floor

Capabilities

Dimmable	No
Type of connection Protective contact Plug (Schuko)	
LED module replaceable	Not replaceable

Certificates & standards

Protection class	1
Type of protection	IP65
Standards	CE/EAC/REACH/ROHS

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075213876	Folding carton box 1	86 mm x 270 mm x 358 mm	2052.00 g	8.31 dm³
4058075213883	Shipping carton box 10	550 mm x 440 mm x 375 mm	21477.00 g	90.75 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.