

# **PRODUCT DATASHEET**RF CLAS P 15 1.6 W/827 E14 FIL

LED Retrofit CLASSIC P | LED lamps, classic mini-ball shape



#### **AREAS OF APPLICATION**

- Perfect for decorative installations
- General illumination
- Outdoor applications only in suitable luminaires
- Domestic applications

### **PRODUCT BENEFITS**

- Very low energy consumption
- Clear lamps with innovative LED "filament" technology
- $\,$   $\,$  No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp

## PRODUCT FEATURES

- Professional LED lamps for line voltage
- Not dimmable
- Mercury-free lamps
- Beam angle: up to 300°
- Lifetime: up to 15,000 h



# **TECHNICAL DATA**

## Electrical data

Rated wattage	1.60 W
Nominal wattage	1.60 W
Nominal voltage	220240 V
Operating frequency	5060 Hz
Power factor λ	> 0.40
Claimed equiv. conventional lamp power	15 W


# Photometrical data

Nominal luminous flux	136 lm
Rated luminous flux	136 lm
Rated color temperature	2700 K
Color rendering index Ra	≥80
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Standard deviation of color matching	≤6 sdcm

# Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

# Dimensions & weight



Overall length	78.0 mm
Diameter	45.0 mm
Outer bulb	P45
Length	78.0 mm

# Lifespan

Nominal lamp life time	15000 h
Rated lamp life time	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

## Additional product data

Base (standard designation)	E14			
Mercury content	0.0 mg			
Mercury-free	Yes			
Design / version	Clear			
Show WEEE picto	Yes			
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value			

#### Capabilities

## Certificates & standards

Energy efficiency class	A++
Energy consumption	2 kWh/1000h

#### Country specific categorizations

ILCOS	DRBP/C-1,3-827-220-240-E14-45	
Order reference	LEDSCLP15 1,6W/	

#### **LOGISTICAL DATA**

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899400320	RF CLAS P 15 1.6 W/827 E14 FIL	Shipping carton box 6	285 mm x 153 mm x 136 mm	5.93 dm³	336.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.