

ILONA-ZOOM

An infinitely adjustable beam from 13 to 48 degrees.

SPECIFICATION:

Dimensions	Ø 52.5
Height	33.2 mm
Fastening	socket
ROHS compliant	yes ⓘ



MATERIALS:


Component	Type	Material	Colour	Finish	Length (mm)
ILONA-ZOOM	Single lens	PMMA	clear		
ILONA-ZOOM-SUB	Sublens	PMMA	clear		

ORDERING INFORMATION:

Quantities for one set:

Single lens	1
Sublens	1

Component		Qty in box	MOQ	MPQ	Box weight (kg)
C17295_ILONA-ZOOM » Box size: 480 x 280 x 300 mm	Single lens	264	33	33	9.7
C17296_ILONA-ZOOM-SUB » Box size: 480 x 280 x 185 mm	Sublens	264	33	33	2.4





See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):





LED V11 HD Gen 8
FWHM / FWTM 21.0 + 46.0° / 45.0 + 88.0°
Efficiency 78 %
Peak intensity 3.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
Bender Wirth: 633d Hekla



Light distribution files




LED V6 HD Gen 7
FWHM / FWTM 14.0 + 48.0° / 30.0 + 84.0°
Efficiency 84 %
Peak intensity 7.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15255_HEKLA-SOCKET-C



Light distribution files



LED V8 Gen7
FWHM / FWTM 16.0 + 46.0° / 35.0 + 83.0°
Efficiency 85 %
Peak intensity 6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15253_HEKLA-SOCKET-A




Light distribution files

OPTICAL RESULTS (MEASURED):




LED Vesta DTW 13mm (21W)
 FWHM / FWTM 25.0 + 46.0° / 55.0 + 90.0°
 Efficiency 77 %
 Peak intensity 2.4 cd/lm
 LEDs/each optic 1
 Light colour/type Tunable White
 Required components:
 C16142_HEKLA-SOCKET-K
 Bender Wirth: 491 Typ L8



Light distribution files





LED Vesta TW 6mm DP
 FWHM / FWTM 15.0 + 48.0° / 32.0 + 84.0°
 Efficiency 84 %
 Peak intensity 7.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C16142_HEKLA-SOCKET-K
 Bender Wirth: 504 Typ L8



Light distribution files



LED Vesta TW 9mm (9W) DP
 FWHM / FWTM 19.0 + 46.0° / 42.0 + 86.0°
 Efficiency 81 %
 Peak intensity 4.2 cd/lm
 LEDs/each optic 1
 Light colour/type Tunable White
 Required components:
 C16142_HEKLA-SOCKET-K
 Bender Wirth: 489 Typ L8





Light distribution files

OPTICAL RESULTS (MEASURED):

CITIZEN


LED CLU02x (LES10)
FWHM / FWTM 21.0 + 47.0° / 42.0 + 86.0°
Efficiency 85 %
Peak intensity 4.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15255_HEKLA-SOCKET-C



Light distribution files

CITIZEN



LED CLU712/713
FWHM / FWTM 19.0 + 47.0° / 37.0 + 84.0°
Efficiency 85 %
Peak intensity 5.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15859_HEKLA-SOCKET-I



Light distribution files



LED CMA1516
FWHM / FWTM 19.0 + 47.0° / 39.0 + 85.0°
Efficiency 85 %
Peak intensity 4.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15256_HEKLA-SOCKET-D





Light distribution files

OPTICAL RESULTS (MEASURED):




LED CMT14xx
FWHM / FWTM 20.0 + 46.0° / 41.0 + 85.0°
Efficiency 85 %
Peak intensity 4.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15255_HEKLA-SOCKET-C



Light distribution files





LED LUXEON CX Plus CoB M02 / M03 (Gen2)
FWHM / FWTM 19.0 + 47.0° / 39.0 + 85.0°
Efficiency 86 %
Peak intensity 4.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15256_HEKLA-SOCKET-D



Light distribution files



LED CxM-9 (13.5x13.5)
FWHM / FWTM 20.0 + 46.0° / 41.0 + 85.0°
Efficiency 86 %
Peak intensity 4.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15255_HEKLA-SOCKET-C




Light distribution files

OPTICAL RESULTS (MEASURED):




LED COB L-Type (LES 9)
 FWHM / FWTM 19.0 + 47.0° / 38.0 + 84.0°
 Efficiency 85 %
 Peak intensity 5.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15858_HEKLA-SOCKET-H



Light distribution files




LED LC003D / LC006D / LC009D / LC013D
 FWHM / FWTM 20.0 + 47.0° / 42.0 + 85.0°
 Efficiency 85 %
 Peak intensity 4.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15255_HEKLA-SOCKET-C



Light distribution files



LED LC010C G2
 FWHM / FWTM 14.0 + 48.0° / 30.0 + 84.0°
 Efficiency 88 %
 Peak intensity 8.5 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15255_HEKLA-SOCKET-C




Light distribution files

OPTICAL RESULTS (MEASURED):




LED MJT COB LES 6
FWHM / FWTM 14.0 + 48.0° / 30.0 + 85.0°
Efficiency 84 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F17435_HEKLA-G2-C



Light distribution files





LED MJT COB LES 9.8
FWHM / FWTM 21.0 + 47.0° / 43.0 + 86.0°
Efficiency 86 %
Peak intensity 4.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15255_HEKLA-SOCKET-C



Light distribution files

XICATO

LED XOB09 Gen1
FWHM / FWTM 19.0 + 47.0° / 40.0 + 85.0°
Efficiency 86 %
Peak intensity 4.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15255_HEKLA-SOCKET-C




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED V4 HD Gen 7
 FWHM / FWTM 12.0 + 46.0° / 25.0 + 76.0°
 Efficiency 82 %
 Peak intensity 12.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15253_HEKLA-SOCKET-A



Light distribution files




LED V6 HD Gen 7
 FWHM / FWTM 14.0 + 47.0° / 30.0 + 81.0°
 Efficiency 88 %
 Peak intensity 8.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15255_HEKLA-SOCKET-C



Light distribution files



LED V9 HD Gen7
 FWHM / FWTM 18.0 + 46.0° / 34.0 + 82.0°
 Efficiency 88 %
 Peak intensity 6.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15859_HEKLA-SOCKET-I



Light distribution files


OPTICAL RESULTS (SIMULATED):



LED Vesta DTW 9mm (4W/6W/12W)
 FWHM / FWTM 18.0 + 46.0° / 36.0 + 84.0°
 Efficiency 86 %
 Peak intensity 5.5 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C16142_HEKLA-SOCKET-K

Bender Wirth: 490 Typ L8


Light distribution files



CITIZEN

LED CLU02x (LES10)
 FWHM / FWTM 20.0 + 46.0° / 37.0 + 80.0°
 Efficiency 78 %
 Peak intensity 4.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15255_HEKLA-SOCKET-C


Light distribution files



CITIZEN

LED CLU03x
 FWHM / FWTM 25.0 + 46.0° / 51.0 + 92.0°
 Efficiency 85 %
 Peak intensity 2.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15859_HEKLA-SOCKET-I


Light distribution files



OPTICAL RESULTS (SIMULATED):

CITIZEN


LED CLU700/701/702/703
 FWHM / FWTM 13.0 + 47.0° / 27.0 + 78.0°
 Efficiency 82 %
 Peak intensity 10 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15255_HEKLA-SOCKET-C



Light distribution files

CITIZEN


LED CLU7A2/7A3
 FWHM / FWTM 13.0 + 48.0° / 26.0 + 83.0°
 Efficiency 88 %
 Peak intensity 10.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15255_HEKLA-SOCKET-C



Light distribution files



LED CMA1306
 FWHM / FWTM 14.0 + 48.0° / 30.0 + 82.0°
 Efficiency 89 %
 Peak intensity 8.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F17439_HEKLA-G2-J




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED CXA/B 13xx
FWHM / FWTM 14.0 + 47.0° / 28.0 + 80.0°
Efficiency 90 %
Peak intensity 9.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15956_HEKLA-SOCKET-J



Light distribution files




LED CXA/B 15xx
FWHM / FWTM 18.0 + 46.0° / 36.0 + 81.0°
Efficiency 89 %
Peak intensity 5.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15256_HEKLA-SOCKET-D



Light distribution files



LED LUXEON CoB 1202/1203
FWHM / FWTM 20.0 + 44.0° / 37.0 + 80.0°
Efficiency 87 %
Peak intensity 5.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F17437_HEKLA-G2-H




Light distribution files

OPTICAL RESULTS (SIMULATED):



LED LUXEON CoB 1204/1205
 FWHM / FWTM 24.0 + 46.0° / 50.0 + 95.0°
 Efficiency 85 %
 Peak intensity 2.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C16142_HEKLA-SOCKET-K




Bender Wirth: 437 Typ L8

Light distribution files




LED CxM-6 (13.5x13.5)
 FWHM / FWTM 14.0 + 46.0° / 30.0 + 81.0°
 Efficiency 90 %
 Peak intensity 8.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F17435_HEKLA-G2-C



Light distribution files



LED COB S-Type (LES 7)
 FWHM / FWTM 16.0 + 48.0° / 30.0 + 80.0°
 Efficiency 89 %
 Peak intensity 7.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15848_HEKLA-SOCKET-G




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED NCSxE17A
FWHM / FWTM 13.0 + 47.0° / 27.0 + 75.0°
Efficiency 88 %
Peak intensity 10 cd/lm
LEDs/each optic 7
Light colour/type White
Required components:



Light distribution files




LED LC003D / LC006D / LC009D / LC013D
FWHM / FWTM 19.0 + 46.0° / 37.0 + 79.0°
Efficiency 77 %
Peak intensity 5.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15255_HEKLA-SOCKET-C



Light distribution files



LED LC010T (Tunable White)
FWHM / FWTM 18.0 + 46.0° / 34.0 + 83.0°
Efficiency 88 %
Peak intensity 6.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C16142_HEKLA-SOCKET-K




Light distribution files

Bender Wirth: 501 Typ L8

OPTICAL RESULTS (SIMULATED):

SAMSUNG


LED LC020C
FWHM / FWTM 14.0 + 46.0° / 28.0 + 77.0°
Efficiency 88 %
Peak intensity 9.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F17438_HEKLA-G2-I



Light distribution files

SAMSUNG

LED LC020T (Tunable white)
FWHM / FWTM 22.0 + 46.0° / 42.0 + 85.0°
Efficiency 86 %
Peak intensity 4.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C16142_HEKLA-SOCKET-K




Light distribution files

Bender Wirth: 501 Typ L8

TRIDONIC

LED SLE G7 LES13
FWHM / FWTM 12.0 + 45.0° / 21.0 + 71.0°
Efficiency 88 %
Peak intensity 16.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F17438_HEKLA-G2-I



Light distribution files

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 7
FI-24100 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)